

```

# -- Configuration Options for PhyPiDAQ
# -----

#
# -- configuration files for hardware devices
#
#DeviceFile: config/ReplayConfig.yaml      # data from File
#optional:
#DeviceFile: config/ToyDataConfig.yaml    # simulated data

# other options(requires connected hardware):
#DeviceFile: config/ADS1115Config.yaml    # 16 bit ADC, I2C bus
#DeviceFile: config/MCP3008Config.yaml    # 10 bit ADC, SPI bus
#DeviceFile: config/MCP3208Config.yaml    # 12 bit ADC, SPI bus
#DeviceFile: config/PSConfig.yaml        # PicoTechnology USB scope
#DeviceFile: config/PSConfig2000.yaml    # PicoTechnology USB scope
220xA
#DeviceFile: config/MAX31865Config.yaml    # Pt 100 sensor
#DeviceFile: config/GPIOCOUNT.yaml        # frequency count
#DeviceFile: config/DS18B20Config.yaml    # digital temperature
sensor
#DeviceFile: config/MAX31855Config.yaml    # thermo element
#DeviceFile: config/BMP180Config.yaml     # pressure/temperature
sensor
DeviceFile: config/INA219Config.yaml     # Voltage/Current sensor
#DeviceFile: config/MMA845xConfig.yaml    # Accelerometer
#DeviceFile: config/MLX90393Config.yaml   # Magnetometer

## an example of multiple devices
#DeviceFile: [config/ADS1115Config.yaml, config/GPIOCOUNT.yaml]

#
# -- configuration options for Channels
#
ChanNams: [I, U]                          # names for channels
ChanUnits: [mA, V]                        # units for channels
#ChanLabels: [U, U]                       # names for channels
#ChanUnits: [V, V]                        # units for channels
ChanColors: [darkblue, sienna]           # channel colours in display

# eventually overwrite Channel Limits obtained from device config
ChanLimits:
- [3.0, 6.0] # chan 0 Current
- [0., 0.6] # chan 1 Voltage
## - [0., 1.] # chan 2

# calibration of channel values
# - null or - <factor> or - [ [ <true values> ], [ <raw
values> ] ]
#ChanCalib:
# - 1. # chan0: simple calibration factor
# - [ [0.,1.], [0., 1.] ] # chan1: interpolation: [true]([<raw>]
)
# - null # chan2: no calibration

# apply formulae to (calibrated) channel values
ChanFormula:

```

```

- c0*1000 # chan0; Current in mA
- c1      # chan1
# - null  # chan2 : no formula

#
# -- configuration options for graphical display
#
Interval: 0.05          # logging interval
#NHistoryPoints: 120    # number of points used in history
buffer
#DisplayModule: DataLogger # history of channel signals
DisplayModule: DataGraphs # text, bar-graph, history and xy-view
Title: "Induced Current and Voltage in Coil" # display title
#XYmode: true          # enable/disable XY-display
## if more than two channels active:
#Chan2Axes: [0, 1, 0]  # assign channels to axes
#yPlots:              # define which axes to show
# - [1, 0]            # in xy-plot
# - [0, 2]
# - [1, 2]

#
# -- configuration options for output to file
#
#DataFile: testfile.csv # file name for output file,
DataFile: null          # null to disable
#CSVseparator: ';'      # field separator, set to ';' for
German Excel

# enable buffering of latest data (depth NHistoryPoints from above)
#bufferData: PhyPiData # file name to track latest data and
eventually
#bufferData: null      # store them, or null to switch off

# control status LEDs
#RunLED: 20           # display run status on GPIO pin 20
#ReadoutLED: 21      # display readout on GPIO pin 21

```