

```

# -- Configuration Options for PhyPiDAQ
# -----
#
# -- configuration files for hardware devices
#
#DeviceFile: config/ReplayConfig.yaml      # data from File
#optional:
#DeviceFile: config/ToyDataConfig.yaml     # simulated data

# other options (requires connected hardware):
DeviceFile: config/ADS1115Config.yaml    # 16 bit ADC, I2C bus
#DeviceFile: config/MCP3008Config.yaml    # 10 bit ADC, SPI bus
#DeviceFile: config/groveADCCConfig.yaml # 12 bit ADC on grove RPI
shield
#DeviceFile: config/MCP3208Config.yaml    # 12 bit ADC, SPI bus
#DeviceFile: config/PSConfig.yaml        # PicoTechnology USB scope
#DeviceFile: config/PSConfig2000.yaml    # PicoTechnology USB scope
220xA
#DeviceFile: config/MAX31865Config.yaml # Pt 100 sensor
#DeviceFile: config/GPIOCount.yaml      # frequency count
#DeviceFile: config/DS18B20Config.yaml # digital temperature
sensor
#DeviceFile: config/MAX31855Config.yaml # thermo element
#DeviceFile: config/BMP180Config.yaml   # pressure/temperature
sensor
#DeviceFile: config/INA219Config.yaml   # Voltage/Current sensor
#DeviceFile: config/MMA845xConfig.yaml # Accelerometer
#DeviceFile: config/MLX90393Config.yaml # Magnetometer

## an example of multiple devices
#DeviceFile: [config/ADS1115Config.yaml, config/GPIOCount.yaml]

#
# -- configuration options for Channels
#

# possibility to overwrite Channel Limits obtained from device
config
ChanLimits:
  - [-40., 40.]    # chan 0
  - [-40., 40.]    # chan 1
## - [0., 1.]      # chan 2

# calibration of channel values
# - null      or - <factor> or - [ [ <true values> ], [ <raw
values> ] ]
#ChanCalib:
#  - 1.          # chan0: simple calibration factor
#  - [ [0.,1.], [0., 1.] ]  # chan1: interpolation: [true]([<raw>]
)
#  - null         # chan2: no calibration

# apply formulae to (calibrated) channel values
ChanFormula:
  - (c0 - c1)*10  # chan0
  - c1*10         # chan1

```

```

# - null           # chan2 : no formula

#
# -- configuration options for graphical display
#
Title: "I, Qc-Charging/Discharging_Capacitor"          # display
title
#ChanLabels: ['I', 'Qc']                                # names for channels
ChanUnits: ['mA', 'muc']                                # units for channels
#ChanLabels: [U, Uc]                                     # names for channels
#ChanUnits: [V, V]                                       # units for channels
ChanNams: [I, Qc]                                       # names for channels
ChanColors: [darkblue, sienna]                           # channel colours in display

Interval: 0.1                                         # logging interval
#NHistoryPoints: 120                                  # number of points used in history
buffer
DisplayModule: DataLogger                            # history of channel signals
#DisplayModule: DataGraphs                          # text, bar-graph, history and xy-
view
#XYmode:      false                                 # enable/disable XY-display
## if more than two channels active:
#Chan2Axes: [0, 1, 0]                                # assign channels to axes
#xyPlots:
# - [0, 1]                                           # define which axes to show
# - [0, 2]
# - [1, 2]                                           # in xy-plot

#
# -- configuration options for output to file
#
DataFile:   C=10micro-R=10k.csv          # file name for output file,
#DataFile:   null                               # null to disable
CSVseparator: ';'                                # field separator, set to ';' for
German Excel

# enable buffering of latest data (depth NHistoryPoints from above)
#bufferData: PhyPiData    # file name to store and track latest data
#bufferData: null        # or null to switch off

# control status LEDs
#RunLED: 20      # display run status on GPIO pin 20
#ReadoutLED: 21 # display readout on GPIO pin 21

```