

```

# -- Configuration Options for PhyPiDAQ
# -----

#
# -- configuration files for hardware devices
#
#DeviceFile: config/ReplayConfig.yaml      # data from File
#optional:
#DeviceFile: config/ToyDataConfig.yaml    # simulated data

# other options(requires connected hardware):
#DeviceFile: config/ADS1115Config.yaml    # 16 bit ADC, I2C bus
#DeviceFile: config/MCP3008Config.yaml    # 10 bit ADC, SPI bus
#DeviceFile: config/groveADCCConfig.yaml  # 12 bit ADC on grove RPI
shield
#DeviceFile: config/MCP3208Config.yaml    # 12 bit ADC, SPI bus
#DeviceFile: config/PSCConfig.yaml        # PicoTechnology USB scope
#DeviceFile: config/PSCConfig2000.yaml   # PicoTechnology USB scope
220xA
#DeviceFile: config/MAX31865Config.yaml   # Pt 100 sensor
#DeviceFile: config/GPIOCCount.yaml      # frequency count
#DeviceFile: config/DS18B20Config.yaml    # digital temperature
sensor
DeviceFile: config/MAX31865Config.yaml    # thermo element
#DeviceFile: config/BMP180Config.yaml     # pressure/temperature
sensor
#DeviceFile: config/INA219Config.yaml     # Voltage/Current sensor
#DeviceFile: config/MMA845xConfig.yaml    # Accelerometer
#DeviceFile: config/MLX90393Config.yaml   # Magnetometer

## an example of multiple devices
#DeviceFile: [config/ADS1115Config.yaml, config/GPIOCCount.yaml]

#
# -- configuration options for Channels
#

# possibility to overwrite Channel Limits obtained from device
config
##ChanLimits:
## - [0., 1.]    # chan 0
## - [0., 1.]    # chan 1
## - [0., 1.]    # chan 2

# calibration of channel values
# - null      or - <factor> or - [ [ <true values> ], [ <raw
values> ] ]
#ChanCalib:
# - 1.                # chan0: simple calibration factor
# - [ [0.,1.], [0., 1.] ] # chan1: interpolation: [true]([<raw>
])
# - null              # chan2: no calibration

# apply formulae to (calibrated) channel values
#ChanFormula:
# - c0 + c1 # chan0
# - c1      # chan1

```

```

# - null          # chan2 : no formula

#
# -- configuration options for graphical display
#
Title: "Temperature"          # display title
#ChanLabels: ['X1', 'X2']    # names for channels
ChanUnits: ['Grad_C']        # units for channels
#ChanLabels: [U, U]          # names for channels
#ChanUnits: [V, V]           # units for channels
ChanNams: [Temp]              # names for channels
ChanColors: [darkblue, sienna] # channel colours in display

Interval: 1.0                 # logging interval
#NHistoryPoints: 120          # number of points used in history
buffer
#DisplayModule: DataLogger    # history of channel signals
DisplayModule: DataGraphs    # text, bar-graph, history and xy-view
#XYmode: false                # enable/disable XY-display
## if more than two channels active:
#Chan2Axes: [0, 1, 0]        # assign channels to axes
#xyPlots:                     # define which axes to show
# - [0, 1]                    # in xy-plot
# - [0, 2]
# - [1, 2]

#
# -- configuration options for output to file
#
DataFile: testfile.csv        # file name for output file,
#DataFile: null               # null to disable
CSVseparator: ';'             # field separator, set to ';' for
German Excel

# enable buffering of latest data (depth NHistoryPoints from above)
#bufferData: PhyPiData        # file name to store and track latest data
#bufferData: null             # or null to switch off

# control status LEDs
#RunLED: 20                   # display run status on GPIO pin 20
#ReadoutLED: 21               # display readout on GPIO pin 21

```