

```

# -- Configuration Options for PhyPiDAQ
# -----

#
# -- configuration files for hardware devices
#
#DeviceFile: config/ReplayConfig.yaml      # data from File
#optional:
#DeviceFile: config/ToyDataConfig.yaml    # simulated data

# other options(requires connected hardware):
#DeviceFile: config/ADS1115Config.yaml    # 16 bit ADC, I2C bus
#DeviceFile: config/MCP3008Config.yaml    # 10 bit ADC, SPI bus
#DeviceFile: config/groveADCCConfig.yaml  # 12 bit ADC on grove RPI
shield
#DeviceFile: config/MCP3208Config.yaml    # 12 bit ADC, SPI bus
#DeviceFile: config/PSCConfig.yaml        # PicoTechnology USB scope
#DeviceFile: config/PSCConfig2000.yaml   # PicoTechnology USB scope
220xA
#DeviceFile: config/MAX31865Config.yaml   # Pt 100 sensor
#DeviceFile: config/GPIOCCount.yaml      # frequency count
#DeviceFile: config/DS18B20Config.yaml   # digital temperature
sensor
#DeviceFile: config/MAX31855Config.yaml   # thermo element
#DeviceFile: config/BMP180Config.yaml     # pressure/temperature
sensor
#DeviceFile: config/INA219Config.yaml    # Voltage/Current sensor
#DeviceFile: config/MMA845xConfig.yaml   # Accelerometer
#DeviceFile: config/MLX90393Config.yaml  # Magnetometer

## an example of multiple devices
DeviceFile: [config/MLX90393Config.yaml, config/VL53LxConfig.yaml]

#
# -- configuration options for Channels
#

# possibility to overwrite Channel Limits obtained from device
config
ChanLimits:
- [0., 3.]      # chan 0
- [-100., 100.] # chan 1
## - [0., 1.]  # chan 2

# calibration of channel values
# - null      or - <factor> or - [ [ <true values> ], [ <raw
values> ] ]
#ChanCalib:
# - 1.                # chan0: simple calibration factor
# - [ [0.,1.], [0., 1.] ] # chan1: interpolation: [true]([<raw>]
)
# - null              # chan2: no calibration

# apply formulae to (calibrated) channel values
ChanFormula:
- sqrt(c0*c0+c1*c1+c2*c2) # chan0
- c3-180                  # chan1

```

```

# - null          # chan2 : no formula

#
# -- configuration options for graphical display
#
Title: "Data from File"          # display title
#ChanLabels: ['X1', 'X2']        # names for channels
#ChanUnits: ['a.U.', 'a.U.']    # units for channels
#ChanLabels: [, U]              # names for channels
ChanUnits: [mT, mm]            # units for channels
ChanNams: [B, d]               # names for channels
ChanColors: [darkblue, sienna]  # channel colours in display

Interval: 0.1                   # logging interval
#NHistoryPoints: 120            # number of points used in history
buffer
#DisplayModule: DataLogger      # history of channel signals
DisplayModule: DataGraphs      # text, bar-graph, history and xy-view
XYmode:      false             # enable/disable XY-display
## if more than two channels active:
#Chan2Axes: [1, 0]             # assign channels to axes
#xyPlots:
#- [1, 0]                       # in xy-plot
# - [0, 2]
# - [1, 2]

#
# -- configuration options for output to file
#
DataFile:  testfile.csv         # file name for output file,
#DataFile:  null                # null to disable
CSVseparator: ';'              # field separator, set to ';' for
German Excel

# enable buffering of latest data (depth NHistoryPoints from above)
#bufferData: PhyPiData         # file name to store and track latest data
#bufferData: null              # or null to switch off

# control status LEDs
#RunLED: 20                    # display run status on GPIO pin 20
#ReadoutLED: 21                # display readout on GPIO pin 21

```